

Deflector channel  
(ESPS-TC-DC)  
offset to allow run-off  
with sealing tape  
(ESPS-SEAL-15/2-6)  
& silicone seal along top

Wraptite  
Frametite  
Tape adhered  
to breather  
membrane and  
sealed over  
the back leg  
of deflector  
channel 150mm  
past the end of  
the channel

Exceeds  
by min  
150mm

25 x 50mm Timber  
batten

Fire stopping  
by others in  
line with fire  
strategy

Glazing

Glazing

Window Cill

600mm max span  
centre to centre  
fixed to kit studs

REV.	AMENDMENTS	DATE	PROJECT	DRAWING I.D.	<small>D:\Users\David\Dropbox\Work\Drawings\Light\spenirowall\top.dwg v16.dwg</small> SPSenirowall Limited Orchard House Aire Valley Business Centre Keighley Yorkshire BD21 3DU Telephone: 01535 661 633 Fax: 01535 661 933
			SPSenirowall Standard Details	PHASE ____ ISSUE ____	
			DESCRIPTION	SYSTEM ID. No.	
			RendaClad onto Timber Battens	SCALE DATE 1:20 @ A4 March 2017	
			DETAIL Wide Window Elevation with Drainage Channel	DRAWN Auto CAD	