



TECHNICAL DATA SHEET

High Performance Mesh– High Impact Mesh– Retromesh– Detail Mesh

Product Code: ESPSM100, ESPSM101, ESPSM103, ESPSM102



SPS ENVIROWALL PROMOTES THE RE-USE –RECYCLING AND RESPONSIBLE DISPOSING OF ALL OF ITS PRODUCT RANGE, VIA THE LOCAL ENVIRONMENTAL RECYCLING SCHEMES.

Characteristics

Glass fibre reinforcement mesh made from glass filament textiles fibres used in to upper layer of basecoats for additional impact resistance and to assist in the prevention of the basecoat render cracking.

Technical Data

Width	1m
Roll Length	50m - High Impact Mesh 25m

Substrate

Substrates must be suitable, stable, flat, clean and dry. Loose render parts can be removed or smoothed if necessary.

Application

Float reinforcing mesh into the top of the base-coat render, ensuring a minimum horizontal and vertical overlap of 100mm. After the application of the main reinforcing mesh, bed on with basecoat 300mm x 500mm minimum pieces of reinforcing mesh diagonally across corners of all wall openings. Bed on internal corner reveal reinforcing strips of mesh (the same depth as the reveal) to all window and door openings; ensure the reinforcing strips return from the corner of the reveals 150mm. Finally apply a 1-2mm slurry coat of basecoat and either sponge flat or leave with a light key ready to receive the selected topcoat finish.

High Impact Mesh adds higher levels of impact resistance and is used behind the main mesh layer butt jointed not overlapped. Generally used from basebead at ground level up to 1.8m to provide higher impact resistance at the more vulnerable zones of a building such as walkways, stairways and public paths.

Detail Mesh is very fine “Gauze” like mesh used to provide mesh reinforcement in tightly detailed areas such as an ashlar groove, where normal mesh would not fold into to create a refined detail.

Storage

Storage conditions Store in a dry place avoiding contamination

Certificates/approvals

Identification

Special Information

Disposal

USE LOCAL RECYCLING SCHEMES IN OPERATION TO RECYCLE MESH OFFCUTS.

Check local landfill requirements for correct disposal. See the SPS Envirowall Limited Health & Safety data sheet on this product for information regarding the safe disposal of this product.

TECHNICAL DATA SHEET

High Performance Mesh– High Impact Mesh– Retromesh– Detail Mesh

Product Code: ESPSM100, ESPSM101, ESPSM103, ESPSM102



The information supplied in this Technical Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.

Our application recommendations, whether verbal, written or as graphics, are given to the best of our knowledge and the state of the art. Information about values, quantities etc. are based on approximate figures. The recommendations do not constitute a legally binding warranty of quality. In particular no liability claims may be based on these recommendations; the provisions of the product liability law remain unaffected. The recommendations do not release the purchaser from his own duty to test the product or from his own responsibility, and in particular they do not release the purchaser from compliance with the relevant technical guidelines, regulations, DIN and laws. Publication of a revised version of this technical information sheet due to technical progress invalidates all older versions of this document